

Product Specification

MT-1820



Specification	
DCV	600m/6/60/600V $\pm(0.5\%+4d)$, 1000V $\pm(1.0\%+6d)$
ACV	6/60/600V $\pm(0.8\%+10d)$, 750V $\pm(1.0\%+10d)$
DCA	600 μ /6000 μ A/60mA/600mA $\pm(1.0\%+10d)$, 6/10A $\pm(1.2\%+10d)$
ACA	600 μ /6000 μ A/60mA/600mA $\pm(1.5\%+10d)$, 6/10A $\pm(2.0\%+15d)$
Resistance	600 Ω $\pm(0.8\%+5d)$, 6k/60k/600k/6M Ω $\pm(0.8\%+4d)$, 60M Ω $\pm(1.2\%+10d)$
Frequency	100/1000/10k/100k/1M/30MHz $\pm(0.5\%+4d)$
Capacitance	40nF $\pm(5\%+30d)$, 400n/4 μ /40 μ F $\pm(3.5\%+8d)$ 200 μ F $\pm(5.0\%+10d)$
Temperature	-20~400°C(0~750°F) $\pm(1.0\%+50d)$, 400~1000°C(750~1832°F) $\pm(1.5\%+15d)$
Continuity with	Y

buzzer	
Diode test	Y
Transistor test	Y
Power source	AAA(1.5V)×2pcs (Not included)
Size	192×95×48 mm
Individual Packing	Color box