

MILAN S.r.l. a socio unico


Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet

tasker® C265 – 2x1,00 mm²

Flexible Double Density Sheath Speaker Cable



CATEGORY
APPLICATION

Flexible Speaker Cable (See Audio Catalogue)
 Professional Loudspeakers and premade cables

- A:** First Soft **PVC** sheath, available in different color.
Outer cable Diam. Ø 7,20 (±0,20) mm.
- B:** Second Soft **PVC** Sheath with different density.
- C:** Core Insulation in **PVC**, colored one Red and one Black.
Diam. Ø 2,60 (±0,20) mm.
- D:** O.F.C. red copper formation 32x0,20 mm.
Nom. Cross section 2x1,00 mm².

MARKING
CUSTOM
PRODUCTION

tasker® C265 2x1.00 mm² – O.F.C. Loudspeaker Cable – Made In Italy
 This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	18,80 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			